

NEC V260X

Order Code: 60003178

NEC V260X Value Projector

Get the Ultimate 3D Experience with a 3D ready DLP®Projector from NEC. DLP®-Link™ technology allows 3D images to be projected with the aid of a single projector and active glasses without special screens, filters or emitters. The impression of 3D is created by the interaction with the active LCD shutter glasses. The easy to set up alternative to traditional 3D stereo projection.

An ideal solution for classrooms, (small) meeting rooms, cross-use (private/professional), mobile / cooperative applications.



DELIVERING GENUINE BENEFITS

Carbon Savings Meter - to encourage the use of EcoMode.

Control and Monitoring - via RS-232.

Green EcoMode Button - on remote.

Higher Efficiency, Lower Power Consumption - full ErP compliance.

Long Lamp Life - up to 5000 hrs.

Virtual Remote - for direct PC control.

3D ready - future-proof DLP®-Link™ technology with 120Hz and Top/Bottom, 60Hz.

Free Download of Multi-Display Management Software - with NaViSet Administrator 2 you can manage all your connected display devices from a centralized location.



OUTSTANDING PERFORMANCE

- **3D Ready DLP®-link™** technology with 120Hz and Top/Bottom, 60Hz
- **Excellent and Brilliant Colours** - due to VIDi technology
- **Contrast 2000:1**
- **Quick Start** - Direct Power Off
- **7W Speaker**
- **Carbon Meter** - indicating the reduced amount of CO₂ emissions by the use of ECO mode



SPECIAL CHARACTERISTICS

3D ready DLP®-Link™, 120Hz and Top/Bottom, 60Hz, 6-segment Colour Wheel, Auto Power Start, BrilliantColor™ and VIDi technology, Carbon Savings Meter, Crestron RoomView, Long Life Lamp, Manual vertical Keystone Correction (V= ±40°), NaViSet Administrator 2, Plug & Play, Quick-Start-/Direct-Power-Off Function, Virtual Remote for direct PC control, 100% recyclable packaging, Downloadable manuals, RoHs compliant, TCO certified, ErP compliant, Intelligent Power Management, WEEE



Energy Efficiency Intelligent Power Management

Ecological Materials 100% recyclable packaging; Downloadable manuals

Ecological Standards RoHs compliant; TCO certified; ErP compliant; WEEE

Technical Specification NEC V260X

IMAGE	
Display	1 x 1.4 cm (0.55") DDR DMD Chip (Aspect Ratio 4:3)
Native Resolution	1024 x 768 (XGA)
Contrast Ratio ¹	2000:1
Brightness ¹	2600 ANSI Lumen
Lamp	180 W AC
Lamp Life [hrs]	3500 (5000 Eco Mode)
Projection Factor	1.95 – 2.15 : 1
Projection Distance [m]	1.2 – 13
Screen Size (diagonal) [cm] / [inch]	Minimum: 76; Maximum: 762
Zoom	Manual
Focus Adjustment	Manual
Supported Resolutions	1920 x 1080; 1600 x 1200; 1400 x 1050; 1280 x 1024; 1280 x 960; 1280 x 720; 1024 x 768; 832 x 624; 800 x 600; 640 x 480
Frequency	Horizontal: 15 – 100 kHz; Vertical: 50 – 120 Hz
CONNECTIVITY	
RGB (analog)	Input: 2 x Mini D-sub 15-pin, compatible to component (YPbPr) Output: 1 x Mini D-sub 15 pin
HDMI™	Input: 1 x HDMI™ (Deep Color, Lip sync)
Video	Input: 1 x RCA
S-Video	Input: 1 x Mini DIN 4-pin
Audio	Input: 2 x 3.5 mm Stereo Mini Jack Output: 1 x 3.5 mm Stereo Mini Jack
PC Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
LAN	1 x RJ45
Video Signals	PAL; PAL60; NTSC; SECAM; NTSC 4.43; PAL-N; PAL-M
REMOTE CONTROL	
Remote Control	Aspect Ratio; Audio Control; Auto Adjust; Automatic Picture Adjustment; Freeze-function; Help-function; ID set; Keystone Correction; Lamp Mode Control; Magnify-function; Picture Adjust; Picture Mode; Picture Mute; Source Select
ELECTRICAL	
Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	233 max.; 210 Eco Mode; 4 Network Stand-By Mode; 0.8 Power Savings Mode
MECHANICAL	
Dimensions (W x H x D) [mm]	310 x 95 x 247 (without lens and feet)
Weight [kg]	2.5
Fan Noise [dB (A)]	31 / 34 (Eco / Normal)
ERGONOMICS	
Safety and Ergonomics	CE; ErP; TÜV GS; RoHS
Speakers [W]	1 x 7 (mono)
WARRANTY	
Projectors	3 years pan-European service
Lamp	6 months, max. 1000 hrs
SHIPPING CONTENT	
Shipping Contents	Projector; IR Remote Control (RD-443E); Mini D-SUB Signal Cable (1.8 m); Power Cord; Users Manual on CD-ROM; Quick Setup Guide; Lens Cap
OPTIONAL ACCESSORIES	
Optional Accessories	3D Starter Kit (NP01SK3D); DLP-Link 3D Glasses (NP01GL); Lamp (NP13LP); Universal Ceiling Mounts (NP01/02/03/04/05UCM)

¹ Compliance with ISO21118-2005