

MP-B20

Media Presentation Button Panel B20

- > Wall mount pushbutton control panel
- > 15 programmable buttons with LED feedback
- > Customizable backlit button labels
- > 5-way navigation pad
- > Volume control knob and LED bargraph
- > Built-in IR receiver and light sensor
- > High-speed Ethernet or Cresnet® communications
- > PoE or Cresnet network powered
- > 3-gang wall box-mountable

The MP-B20 is an enhanced pushbutton control panel designed for installation in a wall or podium. It can be used with any Crestron® control system or presentation switcher, and it provides a perfect complement to any Crestron MPC Media Presentation Controller. Available in white or black, the MP-B20 is constructed to handle the rigors of everyday use in a typical classroom, meeting room, lecture hall, or training facility.

Its 15 “hard key” buttons can be custom programmed to control any function, such as system power, input source selection, transport control, and lighting presets. The 5-way directional navigation pad enables full control of displays and other devices that utilize an onscreen menu. Audio volume and other parameters are adjustable using the control knob and LED bargraph. Custom backlit labeling of each button is facilitated using an assortment of pre-printed labels or Crestron Engraver software.

A built-in IR receiver provides a gateway for RC-5 and Crestron compatible IR wireless remotes. An ambient light sensor is also included, which may be programmed to control the MP-B20's backlight intensity and other customer functions. The MP-B20 can be powered through the network wiring using either Cresnet® or PoE (Power over Ethernet), requiring just one wire for operation.

SPECIFICATIONS

Communications

Ethernet: 10/100 Mbps, auto-switching, auto-negotiating, auto-discovery, full/half duplex, DHCP, IEEE 802.3af and 802.3at Type 1 compliant

Cresnet®: Cresnet slave mode

USB: USB 1.1 device port for computer console (firmware update)

IR: Built-in RC-5 compatible IR receiver

Connectors

NET: (2) sets of (4) captive screw terminals;
Cresnet slave port with parallel pass-through

LAN PoE: (1) 8-wire RJ45, female;
10Base-T/100Base-TX Ethernet port, Power over Ethernet compliant

Computer: (1) USB Type B, female (behind front cover);
USB 1.1 computer console port for firmware update

Ground: (1) flying lead, chassis ground wire



Controls & Indicators

Hard Keys: (15) Programmable pushbuttons with backlit labeling

Feedback Indicators: (15) Programmable red LEDs (1 per hard key)

Navigation Pad: (5) Programmable pushbuttons for 4-way directional navigation and “enter”

VOLUME: (1) Programmable continuous turn rotary encoder

Bargraph: (1) Programmable red 5-segment LED bargraph

HW-R: (1) Recessed miniature pushbutton for hardware reset

SETUP: (1) Recessed miniature pushbutton (behind front cover) for setting up connection with the control system via Cresnet or Ethernet

LAN PoE (rear): (2) green LEDs, bottom LED indicates link status, top LED indicates Ethernet activity

Light Sensor

Photosensor, programmable for auto-dimming of the backlight and other functions

IR Receiver

Reception Frequency: 36 to 38 kHz IR

Formats: Crestron format, RC-5

Range: Up to 50 ft line of sight (typical), dependent upon angle, obstructions, IR interference, and IR remote signal strength

Power Requirements

Cresnet Power Usage: 4 Watts (0.17 Amps @ 24 Volts DC)

Power over Ethernet: IEEE 802.3at Type 1 (802.3af compatible) Class 2 (6.49W) PoE Powered Device

Note: If both PoE and Cresnet power are connected, power will be drawn from Cresnet.

MP-B20 Media Presentation Button Panel B20

Environmental

Temperature: 32° to 104°F (0° to 40°C)
Humidity: 10% to 90% RH (non-condensing)
Heat Dissipation: 14 BTU/hr

Enclosure

Faceplate: Plastic, black or white, with polycarbonate label overlay
Chassis: Plastic with metal mounting plate
Mounting: Mounts in a 3-gang electrical box or mud ring, 2 inch (51 mm) or greater mounting depth recommended

Dimensions

Height: 4.50 in (115 mm)
Width: 6.70 in (171 mm)
Depth: 2.23 in (57 mm)

Weight

17 oz (467 g)

MODELS & ACCESSORIES

Available Models

MP-B20-B-T: Media Presentation Button Panel B20, Black
MP-B20-W: Media Presentation Button Panel B20, White

Available Accessories

MP/MPC/IPAC FRONT LABEL: Custom Engravable Backlit Labels
TTK-MP/MPC/IPAC: Table Mount Kit
SMK-MP/MPC/IPAC: Swivel Mount Kit
PWE-4803RU: PoE Injector
CEN-SW-POE-5: 5-Port PoE Switch
CEN-SWPOE-16: 16-Port Managed PoE Switch
CRESNET-NP: Cresnet® Control Cable, Non-Plenum
CRESNET-P: Cresnet® Control Cable, Plenum-Rated
CRESNET-HP-NP: Cresnet® “High-Power” Control Cable, non-plenum

Notes:

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron, the Crestron logo, and Cresnet, are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2015 Crestron Electronics, Inc.



MP-B20-W — Shown in White

